

# Oasis Sykes Pumps



**GP200M**

The general purpose industry standard for contractors, water authorities and local agencies, the Oasis Sykes GP pump range has evolved over 30 years of heavy duty pump manufacture

Specifically designed for arduous applications, the Oasis Sykes GP200M pump is typical of the range, utilizing tried and tested components, selected to ensure maximum reliability.

Used wherever there is a need for positive self-priming the GP200M incorporate the unique Oasis Sykes vacuum system, enabling the pump to prime and re-prime fully automatically from dry, and operate with the suction intake intermittently exposed to atmosphere

- **General purpose- handles everything from clear water to heaviest sludge and slurry**
- **Hard wearing cast iron parts and corrosion resistance materials throughout**
- **Four wheeled site trailer/ skid mounted version**
- **Sustained performance**
- **Ease of maintenance shaft seals can be changed in minutes**
- **Automatic priming and re-priming**
- **Hours of unattended operation or intermittent flow**
- **Low centre of gravity easy and stable to tow.**

Performance	GP200	GP200M
Max. Head	35m	43m
Max. Flow	138 l/s	161 l/s
Max. Solid	75 mm	75mm

### Pipe Connection

Suction	200 mm (8")
Delivery	200 mm (8")

### Pump Material

Main pump SG grade iron

### Weight (Typical)

1545 kg with fuel  
1440 kg without fuel

### Chassis

4 wheeled site trailer

### Fuel Tank

Approx. 183 liters with cleaning and flushing facility

### Engine

GP200 Lister-Petter CD4 water cooled- 70bhp @1800rpm

GP200M IVECO TRIER 3- water cooled- 74bhp @1800rpm

### Prime System

Flood lubricated rotary vacuum pump of nominal displacement 60 cfm incorporating non-return valve

### Shaft Seal

- Oasis Sykes patented vacuum/pressure seal
- Spring loaded
- Easy repacking
- \* Single ring of packing
- \* No adjustments necessary
- \* Chrome oxide coating on wear ring

